



| REVISIONS | | | |
|-----------|------------------------|-----------|----------|
| REV. | DESCRIPTION | DATE | ECO. NO. |
| - | Release for production | 01-Jul-21 | |
| | | | |



| 行程代码 | 行程 (mm) | 尺寸A (mm) | 尺寸B (mm) |
|------|---------|----------|----------|
| 302 | 12.7 | 25.7 | 1.5 |
| 303 | 19.05 | 32 | 7.9 |
| 304 | 25.4 | 38.4 | 14.2 |
| 305 | 31.75 | 44.7 | 20.6 |
| 306 | 38.1 | 51.1 | 26.9 |
| 307 | 50.8 | 63.8 | 39.6 |
| 308 | 63.5 | 76.5 | 52.3 |

| 规格说明Specification | |
|----------------------------|---------------|
| 工作电压 Operating Voltage | ??? V |
| 每相电阻 Resistance Per Phase | ??? OHMS±10% |
| 绝缘电阻 Insulation Resistance | 20M OHMS |
| 功耗 Power Consumption | ??? W |
| 最小推力 Minimum Force(300PPS) | ??? N |
| 导程 Lead | ??? mm |
| 步长 Step | ??? mm |
| 步距角 Step Angle | 1.8° |
| 额定电流 Rated Current | ??? A |
| 工作温度 Operating Temperature | -40° to +55° |
| 环境温度 Storage Temperature | -40° to +100° |
| 其它 Others | |

描 图

描 校


底图存放

签 字



日期

客 户
Customer

Wiring Diagram 接线图



Exciting Sequence 励磁顺序

| | | | | |
|----|---|---|---|---|
| 伸出 |  | | | |
| A+ | + | - | - | + |
| A- | - | + | + | - |
| B+ | + | + | - | - |
| B- | - | - | + | + |
| 缩回 |  | | | |

STANDARD BLOCK TOLERANCES:UNLESS OTHERWISE SPECIFIED

| | | INCH | | MM |
|-----------|--------|--------|-------|--------|
| DECIMALS: | X | ±.020 | X | ±0.38 |
| DECIMALS: | X.X | ±.015 | X.X | ±0.25 |
| DECIMALS: | X.XX | ±.010 | X.XX | ±0.13 |
| DECIMALS: | X.XXX | ±.005 | X.XXX | ±0.013 |
| DECIMALS: | X.XXXX | ±.0005 | | |
| ANGLES: | | ±2° | | |

Drawn By

SY

Date

01-Jul-21

Unit mm

常州惠勒电机有限公司
Changzhou Wheeler Motor CO., LTD
常州市新北区新桥工业园区镜湖路28号
No.28,Jinghu Road,Xinqiao Industrial Park,
Xinbei District,Changzhou,213125
TEL:0519-83252878, 85102562
FAX:0519-83252220
EMAIL:info@wheeler.com.cn
www.wheeler.com.cn

Scale: A4

Rev: -

Sheet 1 of 1

WHEELER™

常州惠勒电机有限公司

DWG.NO.

57CA4X-XX-XXX